



TECHNICAL DATA SHEET

ULTRA-LITE 2K GOLD

PRODUCT DESCRIPTION

Concept's Ultra-Lite 2K Gold is manufactured from a blend of high grade resins to maximise its performance. It is ideally suited for use in automotive low bake ovens and under Concept 2K paint finishes.

PRODUCT AND ADDITIVES

- Concept Ultra-Lite 2K Gold
- Concept Body Filler Hardener

SUITABLE SUBSTRATES



- Most metal surfaces.
- Glass reinforced polyester.

MIXING RATIO

- 40 – 50 parts of Concept Ultra-Lite 2K Gold.
- 1 part Concept Body Filler Hardener.
- Thoroughly mix until an even colour is obtained.

APPLICATION

- All surfaces must be thoroughly sanded prior to application.
- Apply putty to surface with firm pressure, do not apply heavy coats. Apply thin layers working to a smooth surface.

DRYING	<ul style="list-style-type: none"> • 20 - 30 minutes at 25°C. 	
SANDING:	<ul style="list-style-type: none"> • Use 36/40 grade paper and finish off with 100/120 grit fre-cut. Sand thoroughly before applying finish coat. 	

TECHNICAL INFORMATION

COLOUR:	Off White
PACKAGING:	3.5 KG, 9KG Hardener: 75GMS, 120GMS
ITEM CODE:	A03/ULN (Hardener: A03E/BODYHARD)
SHELF LIFE:	12 Months

The above information is reliable and accurate to the best of our knowledge at the time of preparation. Any recommendations or suggestions made are without warranty or guarantee. Users assume all responsibility since the conditions of use are beyond our control.

REVISED: 1 December 2004

REPLACES ISSUE: 1 July 2003